



Allstate Gasket & Packing, Inc.
 31 Prospect Place • Deer Park, NY 11729
 Tel: (631) 254-4050 Fax: (631) 254-4330
www.allstategasket.com

ALLSTATE GASKET PRODUCT INFORMATION

STYLE 1206 - NYLON INSERTED DIAPHRAGM

	MATERIAL	NEOPRENE POLYMER, NYLON FABRIC INSERTION 14.5oz.
	COLOR	BLACK
	HARDNESS	60+-5 DURO SHORE A
	TENSILE	1,000 PSI
	ELONGATION	500%
	TEMPERATURE	-20°F to +200°F
	FINISH	SMOOTH
	TEST METHOD	Mullen Burst Test Rating Over 1000psi with 1" Square Opening
	MEETS SPECIFICATIONS	ASTM D2000-M2-BC607-A14-B14-F17

RECOMMENDED USES:

To control valves, regulators and pumps. It is an excellent weatherstripping material.

- Available in full rolls
- Available in trimmed sheets
- Can be supplied in cut-to-width strips
- Pressure sensitive adhesive backing is also available
- Sizes vulcanized to infinity

IMPORTANT DISCLAIMER: All information provided is for reference. Always perform your own tests and acquire further information to determine product suitability. While we make effort to provide accurate information, we cannot be held responsible for errors either of omission or typographical. Allstate Gaskets assumes no responsibility for the use or suitability of any product. This is a general guide and should not be the sole means of selecting or rejecting this material. Results listed are typical and not minimums. Requirements should not be based on typical values.