



Allstate Gasket & Packing, Inc.
 31 Prospect Place • Deer Park, NY 11729
 Tel: (631) 254-4050 Fax: (631) 254-4330
www.allstategasket.com

STYLE 1207 EPDM-NYLON INSERTED DIAPHRAGM

	MATERIAL	Ethylene Propylene Diene Methylene Terpolymer (EPDM) Nylon Fabric Insertion (14.5oz.).
	COLOR	BLACK
	HARDNESS	60 Shore A +/-5
	TENSILE	1,000 PSI
	ELONGATION	500%
	OPERATING TEMPERATURE	220°F (104.5°C)
	FINISH	SMOOTH
	TEST METHOD	Mullen Burst Test Rating Over 1000psi with 1" Square Opening

RECOMMENDED USES:

Valves, Pumps, Conveyor Belts, Gaskets, etc. EPDM rubber is resistant to weather, sunlight, industrial chemicals and petroleum.

- Available in full rolls
- Available in trimmed sheets
- Can be supplied in cut-to-width strips
- Pressure sensitive adhesive backing is also available
- Sizes vulcanized to infinity

IMPORTANT DISCLAIMER: All information provided is for reference. Always perform your own tests and acquire further information to determine product suitability. While we make effort to provide accurate information, we cannot be held responsible for errors either of omission or typographical. Allstate Gaskets assumes no responsibility for the use or suitability of any product. This is a general guide and should not be the sole means of selecting or rejecting this material. Results listed are typical and not minimums. Requirements should not be based on typical values.