



Allstate Gasket & Packing, Inc.
 31 Prospect Place • Deer Park, NY 11729
 Tel: (631) 254-4050 Fax: (631) 254-4330
www.allstategasket.com

STYLE 1208 NITRILE – NYLON INSERTED DIAPHRAGM

	MATERIAL	Nitrile (Buna N) with Polymer Nylon Fabric Insertion (14oz.).
	COLOR	BLACK
	HARDNESS	60 Shore A +/-5
	TENSILE	1,000 PSI
	ELONGATION	500%
	TEMPERATURE	-20°F to +200°F
	FINISH	SMOOTH
	TEST METHOD:	Burst Test Across 2" Opening 7.0 Mpa (1015 PSI) 1/8" - 2 Ply

RECOMMENDED USES:

For applications requiring a high degree of resistance to oils, fuels and solvents at a reasonable cost.

- Available in full rolls
- Available in trimmed sheets
- Can be supplied in cut-to-width strips
- Pressure sensitive adhesive backing is also available
- Sizes vulcanized to infinity

IMPORTANT DISCLAIMER: All information provided is for reference. Always perform your own tests and acquire further information to determine product suitability. While we make effort to provide accurate information, we cannot be held responsible for errors either of omission or typographical. Allstate Gaskets assumes no responsibility for the use or suitability of any product. This is a general guide and should not be the sole means of selecting or rejecting this material. Results listed are typical and not minimums. Requirements should not be based on typical values.